

Mobil Delvac XHP Ultra 5W-30

Synthetic Diesel Engine Oil

Product Description

Mobil Delvac XHP Ultra 5W-30 is a synthetic, extra high performance diesel engine oil engineered to provide outstanding protection and fuel economy for modern heavy duty diesel engines used in severe on highway applications. This diesel engine oil is designed using advanced technology base oils which provide excellent low temperature fluidity, high temperature viscosity retention, volatility control, and contribute to fuel economy improvement. These base oils also feature an advanced additive system, which provides the highest level of protection to all parts of the engine.

Features & Benefits

High output, low emission diesel engines significantly increase the demands on engine lubricants. Tighter engine designs reduce oil consumption, resulting in less fresh oil make-up to replenish depleted additives. Thermal stresses on the lubricant are increased with the use of intercoolers and turbochargers. Higher fuel injection pressure and retarded timing improve burn efficiency, but also increase engine temperatures, volatility, and soot loading of the oil. The advanced technology in Mobil Delvac XHP Ultra 5W-30 delivers exceptional performance and is approved as the initial fill for Mercedes Benz Actros diesel engines. The key benefits include:

Features	Advantages & Potential Benefits
Outstanding protection against oil thickening, high temperature deposits, sludge build-up, oil degradation and corrosion Excellent anti-wear and anti-scuff properties	Prolonged engine life Less wear Outstanding control of high temperature deposits Extended oil life above OEM recommended Oil Drain Intervals(ODI) Excellent protection against ring sticking
Extended TBN Reserve	Long-term deposit/wear control Extended oil drain potential
Excellent low temperature properties	Excellent pumpability and oil circulation Start-up wear protection
Stay-in-grade shear stability Very low volatility	Reduces viscosity breakdown and helps reduce oil consumption under heavy duty, high temperature operating conditions
Advanced formulation viscometrics	Increased fuel economy

Applications

- Naturally aspirated and turbo-charged diesel engines built by Mercedes Benz and MAN manufacturers
- On highway light and heavy duty trucking



Specifications & Approvals

Mobil Delvac XHP Ultra 5W-30 has the following builder approvals:

Daimler Chrysler MB 228.5	X
MAN M3277	X

Typical Properties

Mobil Delvac XHP Ultra 5W-30

SAE Grade	5W-30
Viscosity, ASTM D 445	
cSt @ 40°C	68
cSt @ 100°C	11.8
Viscosity Index, ASTM D 2270	172
Sulfated Ash, wt%, ASTM D 874	1.8
Total Base # , mg KOH/g, ASTM D 2896	15.5
Pour Point, °C, ASTM D 97	-33
Flash Point, °C, ASTM D 92	235
Density @ 15°C kg/l, ASTM D 4052	0.87

Health & Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Delvac are trademarks of ExxonMobil Corporation, or one of its subsidiaries.

